



Cool-Vent™

Packaging & Weight Chart

SIZE	FOAM	LTRR	PCS	LBS/PC	LBS/SF	LBS/PAL
7/16 OSB						
2.5	1.0	5.7	19	60.30	1.884	1145.7
3.0	1.5	8.6	16	62.90	1.966	1006.4
3.5	2.0	11.4	13	65.50	2.047	851.5
4.0	2.5	14.4	12	68.10	2.128	817.2
4.1	2.6	15.0	11	68.62	2.144	754.8
4.5	3.0	17.4	10	70.70	2.209	707.0
5.0	3.5	20.5	9	73.30	2.291	659.7
5/8 OSB						
2.6	1.0	5.7	18	74.30	2.322	1337.4
3.1	1.5	8.6	15	76.90	2.403	1153.5
3.6	2.0	11.4	13	79.50	2.484	1033.5
4.1	2.5	14.4	11	82.10	2.566	903.1
4.2	2.6	15.0	11	82.62	2.581	908.8
4.6	3.0	17.4	10	84.70	2.647	847.0
5.1	3.5	20.5	9	87.30	2.728	785.7
5/8 PLY						
2.6	1.0	5.7	18	66.80	2.088	1202.4
3.1	1.5	8.6	15	69.40	2.169	1041.0
3.6	2.0	11.4	13	72.00	2.250	936.0
4.1	2.5	14.4	11	74.60	2.331	820.6
4.2	2.6	15.0	11	75.12	2.347	826.3
4.6	3.0	17.4	10	77.20	2.413	772.0
5.1	3.5	20.5	9	79.80	2.494	718.2
3/4 PLY						
2.7	1.0	5.7	17	76.80	2.400	1305.6
3.2	1.5	8.6	14	79.40	2.481	1111.6
3.7	2.0	11.4	12	82.00	2.563	984.0
4.2	2.5	14.4	10	84.60	2.644	846.0
4.3	2.6	15.0	11	85.12	2.660	936.3
4.7	3.0	17.4	9	87.20	2.725	784.8
5.2	3.5	20.5	8	89.80	2.806	718.4

COOL-VENT IS ONLY MANUFACTURED IN THE SIZES LISTED IN THE CHART ABOVE. R-VALUES OTHER THAN THOSE LISTED ABOVE CAN BE ACHIEVED BY INSTALLING A MULTI LAYER SYSTEM CONSISTING OF AN ADDITIONAL LAYER OF FLAT POLYISO UNDER COOL-VENT.

HUNTER
Energy Smart Polyiso

888-746-1114 • WWW.HUNTERPANELS.COM