



HUNTER

# FOIL-GRIP™ 1402

Indoor/Outdoor

## TECHNICAL DATA SHEET

*Foil-Grip 1402 is a pressure sensitive, 40-year cycle, general purpose rolled sealant. It provides an instant water resistant grip to most surfaces including Hunter Xci polyiso products.*

### FEATURES AND BENEFITS

- Convenient size rolls
- Firm adhesion over wide temperature range
- Excellent UV resistance
- Can be integrated with Hunter Xci Foil Class A to create a 3-in-1 air/water/thermal barrier solution

### INSTALLATION

Surfaces shall be clean, sound and dry. Cut CCW Foil-Grip 1402 to size. Position in place and remove release liner. Install tape smooth and flat against surface, avoiding formation of wrinkles or bubbles. Press tape in place, especially at edges and corners with seam roller or with a squeegee. Overlap neighboring pieces of tape 3" minimum at horizontal splices and 5" minimum at vertical splices. Sequence installation of Foil-Grip 1402 to form shingled laps. In cold weather, store Foil-Grip 1402 in a heated area at 50°F or higher for at least 16 hours before use. In temperatures between 40 – 25 degrees apply Cav-Grip Primer to foil surface prior to tape installation. Do not apply Foil-Grip 1402 in temperatures below 25 degrees.

### PART NUMBERS

304093	1 Case w/ (24) 2" x 100' Rolls (Non-printed)
304094	1 Case w/ (16) 3" x 100' Rolls (Non-printed)
304095	1 Case w/ (12) 4" x 100' Rolls (Non-printed)
304096	1 Case w/ (8) 6" x 100' Rolls (Non-printed)
304083	1 Roll 36" x 100' (Non-printed)
304099	1 Case w/ (24) 2" x 100' Rolls (Printed)
304100	1 Case w/ (16) 3" x 100' Rolls (Printed)



### TECHNICAL DATA

Appearance	Mill finish aluminum substrate with gray adhesive/sealant
Backing	Aluminum
Thickness	17 mils
Sealant Material	Modified butyl
Peal Strength	16 lbs. per linear inch
Tensile Strength	955 psi avg.
Elongation	560% avg.
Flexibility	Excellent, no cracking
Bonding Time	Instant high tack, full bond 24 hours
Time to Test	Immediate
Service Temperature	-20°F to 180°F
Weather Resistance	Passes 2000 hours QUV (When tested in accordance with ASTM G 53)
Mildew Resistance	Mold & mildew resistant
VOC	0 g/l
Pressure Classes	SMACNA 1/2, 1, 2, 3, 4, 6 and 10 inches w.g.
Seal Classes	SMACNA A, B, C
Packaging	100-ft. rolls in 2, 3, 4, 6 and 36-inch widths 400 ft <sup>2</sup> per case
Application Temperature	25°F to 110°F (1.7°C to 44°C)

## PRECAUTIONS

Surfaces must be clean and free of moisture and contamination. Do not apply this product in areas where temperatures will exceed 180°F. Keep out of the reach of children. Review MSDS for safety information prior to use. DO NOT use where acidic or alkaline chemicals are present (ie., lab fume hood, vents, etc.)

For Industrial Professional Use Only.

## SPECIFICATION / STANDARDS COMPLIANCE

Property	Method	Results
VOC Limitation	SCAQMD Rule 1168	Pass
City of Los Angeles Approval RR#8069	-	Pass

## STORAGE

Temperature	50°F to 90°F DO NOT FREEZE
Shelf Life	24 months
Flammability	Non-flammable

